



# MATERIAL SAFETY DATA SHEET

## LPS<sup>®</sup> PF<sup>®</sup> HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

### Section 1 • Product and Company Identification

**Product Name:** LPS<sup>®</sup> PF<sup>®</sup> HP

**Part Number:** 62001, 62005, 62055, C62001, C62005, C62055

**Chemical Name:** Hydrocarbon Mixture

**Product Use:** An industrial grade solvent specially formulated to remove heavy-duty grease build-up on power cables, power cable components, and other power utility applications.

**Manufacturer Information:** LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084

**TEL:** USA & Canada: 1 800 241-8334  
Outside USA and Canada +1 770-243-8800

**FAX:** USA & Canada: 1 800 543-1563  
Outside USA and Canada +1 770-243-8899

**Emergency Telephone Number:** Chemtrec: USA&Canada 1-800-424-9300  
Outside USA and Canada: +1 (703) 527-3887

**Website:** <http://www.lpslabs.com>

#### PLAIN LANGUAGE HAZARD SUMMARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably will not help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, do not hesitate to call us at 770-243-8800.

##### Worker Toxicity

PF<sup>®</sup> HP is designed to remove heavy-duty grease build-up on power cables, power cable components, and other power utility applications. It contains petroleum hydrocarbons that can be irritating to skin. We suggest you wear gloves and avoid extended exposure to unprotected skin. Don't get it in your eyes (it stings), or breath large amounts of the vapor, (it will dry out your nasal passages and if you breathe large amounts in poorly ventilated areas it can make you dizzy and even sick). Don't use PF<sup>®</sup> HP for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator or even a self-contained breathing apparatus may be necessary. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

##### Flammability

PF<sup>®</sup> HP is combustible having a flash point above 140°F. Do not use on red-hot metal surfaces. Store product away from heat sources and do not use on live electrical equipment.

##### Disposal

If you spill PF<sup>®</sup> HP notify the proper environmental or safety department at your company right away. Keep out of surface waters, sewers, and water supplies.



# MATERIAL SAFETY DATA SHEET

LPS<sup>®</sup> PF<sup>®</sup> HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

---

## Section 2 • Hazards Identification

---

*This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

### Emergency Overview:

**Aerosol:** Not Applicable

**Bulk:** DANGER: Combustible. Harmful or fatal if swallowed.

**Primary route(s) of entry:** Skin and eye contact. Inhalation.

### Potential Acute Health Effects:

**Eyes:** Irritating to eyes.

**Skin:** Repeated exposure may cause skin dryness or cracking.

**Inhalation:** Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

**Ingestion:** Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

### Potential Chronic Health Effects:

**Carcinogenic Effects:** NTP: No IARC: No OSHA: No ACGIH: No

**Mutagenic Effects:** None

**Teratogenic Effects:** None

**Target Organs:** None

**Medical conditions aggravated by exposure:** Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

### Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

---

## Section 3 • Composition / Information on Ingredients

---

Component	CASRN	Weight Percent
Solvent Naphtha	64742-94-5	70– 80 %
Naphtha (Petroleum), Hydrotreated Heavy	64742-48-9	10 – 20 %
1,2,4-Trimethylbenzene	95-63-6	1 – 2 %



# MATERIAL SAFETY DATA SHEET

## LPS® PF® HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

### Section 4 • First Aid Measures

- Eyes:** Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.
- Skin:** Remove contaminated shoes and clothing. Rinse affected area thoroughly with water. Do not use ointments. Seek medical attention if irritation persists.
- Inhalation:** Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.
- Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention immediately.

### Section 5 • Fire Fighting Measures

- Products of Combustion:** Carbon monoxide and carbon dioxide.
- General Fire Hazards:** High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers.
- Firefighting media:** SMALL FIRE: Use DRY chemical powder.  
LARGE FIRE: Use CO<sub>2</sub>, water spray, fog or foam. Cool containing vessels with water to prevent pressure build-up, auto ignition or explosions.
- Sensitivity to Impact:** None    **Sensitivity to Static Discharge:** Yes
- Protection Clothing (Fire):** Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.
- Special Remarks on Explosion Hazards:** None

### Section 6 • Accidental Release Measures

- |                               |   |  |
|-------------------------------|---|--|
| <b>Containment Procedures</b> | <b>Small Spill and Leak:</b>  | Eliminate ignition sources. Absorb with an inert material and dispose of properly.   |
|                               | <b>Large Spill and Leak:</b>  | Eliminate ignition sources. Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal. |
| <b>Clean-Up Procedures</b>    | Recover free product and place in suitable container for disposal.                                    |  |
| <b>Evacuation Procedures</b>  | Ventilate area of leak or spill. Keep unnecessary and unprotected people away.                        |  |
| <b>Special Procedures</b>     | Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment during cleanup. |  |



# MATERIAL SAFETY DATA SHEET

## LPS® PF® HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

### Section 7 • Handling and Storage

**Handling:** DO NOT spray into or around ignition sources. Do not allow material to come into contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

**Storage:** Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F and 120°F (4.4°C and 49°C).

**Precautions to be taken in handling and storage:** Store all materials in a dry, well-ventilated area. Avoid breathing vapors.

### Section 8 • Exposure Controls / Personal Protection

#### Exposure Guidelines:

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH-TLV	ACGIH-STEL	NIOSH
Solvent Naphtha	64742-94-5	Not Established	Not Established	Not Established	Not Established	100 mg/m <sup>3</sup> * 17 ppm*
Naphtha (Petroleum), Hydrotreated Heavy	64742-48-9	171 ppm*	Not Established	Not Established	Not Established	Not Established
1,2,4-Trimethylbenzene	95-63-6	25 ppm	Not Established	25 ppm 17 ppm*	Not Established	Not Established

\*Supplier Recommendation

**Engineering Controls:** Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines listed above.

#### Personal Protection:

**Eye protection** Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.

**Hand protection** Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, use chemical resistant gloves conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.

**Respiratory protection** Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e., organic vapor cartridge).

**General Hygiene Considerations** Wash thoroughly after handling. Have eye-wash facilities immediately available.



# MATERIAL SAFETY DATA SHEET

## LPS® PF® HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

### Section 9 • Physical and Chemical Properties

<b>Appearance:</b>	Liquid	<b>Color:</b>	Colorless
<b>Odor:</b>	Characteristic	<b>Evaporation Rate:</b>	0.1 (BuAc=1)
<b>Solubility Description:</b>	Not soluble in water	<b>Flash Point:</b>	>61°C(142°F)
<b>Boiling Point:</b>	160°C (361 °F)	<b>Flash Point Method:</b>	TCC
<b>Specific Gravity (H2O=1):</b>	0.85 – 0.87 @ 20°C	<b>Decomposition Temperature:</b>	Not Established
<b>Vapor Density (air = 1):</b>	>1	<b>Auto Ignition Temperature:</b>	>260°C(500°F)
<b>Vapor Pressure:</b>	> 0.1 mmHg @ 20°C	<b>Flammable limits (estimated):</b>	LOWER: 0.7% UPPER: 11.7%
<b>Rule 1171 PPc:</b>	Not Established	<b>Partition Coefficient (octanol/water):</b>	Not Established
<b>V.O.C. Content:</b>	Aerosol: Not Applicable Bulk: 100%, 860 g/L, 7.2 #/gal per CARB/OTC/EPA Regulations	<b>Odor Threshold:</b>	Not Established
<b>Melting Point:</b>	Not Established	<b>Viscosity:</b>	Not Established
<b>pH:</b>	Not Applicable	<b>Volatiles:</b>	100%
<b>Heat of combustion:</b>	Aerosol: Not Applicable Bulk: Not Established		

### Section 10 • Stability and Reactivity

<b>Chemical Stability:</b>	Product is stable under recommended storage conditions.
<b>Conditions to Avoid:</b>	Keep away from heat and ignition sources.
<b>Incompatibility:</b>	Reactive or incompatible with oxidizing agents and strong acids.
<b>Hazardous Decomposition:</b>	These products are carbon oxides ( CO, CO2)
<b>Hazardous Polymerization:</b>	Will not occur.

### Section 11 • Toxicological Information

#### Acute and Chronic Toxicity

#### A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.



# MATERIAL SAFETY DATA SHEET

## LPS® PF® HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

### B: Component Analysis

Component	CASRN	LC-50	LD-50
Solvent Naphtha	64742-94-5	>590 mg/m <sup>3</sup> /rat/4hr	>2 mL/kg/dermal/rabbit
Naphtha (Petroleum), Hydrotreated Heavy	64742-48-9	Not Established	> 10000mg/kg/oral* >3160 mg/kg/dermal*
1,2,4-Trimethylbenzene	95-63-6	18000 mg/m <sup>3</sup> /rat/4hr	6900 mg/kg/oral/mouse

\* Supplier Data

### Section 12 • Ecological Information

**Mobility:** Volatile. Not expected to partition to sediment. **Persistence and degradability:** Slightly biodegradable

**Bioaccumulative potential:** Low bioaccumulation potential **Other adverse effects:** None known

Ecological studies have not been conducted for this product. The following information is available for component(s) of this product.

#### Ecotoxicity:

Effect on Organisms	Component	CASRN	Test	Species	Results
Acute Toxicity on Fishes					No Data Available
Acute Toxicity on Daphnia					
Bacterial inhibition					
Growth inhibition of algae					
Bioaccumulation in fish					

\* Supplier Data

### Section 13 • Disposal Considerations

**Waste Status:** In its purchased form, this material does not meet the definition of a RCRA hazardous waste.

**Disposal:** Waste must be disposed of in accordance with national, regional and local environmental control regulations.

**Note:** Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.

### Section 14 • Transport Information

**Bulk versions of this product are not regulated by any mode of transportation.**



# MATERIAL SAFETY DATA SHEET

LPS<sup>®</sup> PF<sup>®</sup> HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

## Section 15 • Regulatory information

### U.S. Federal Regulations

RCRA Hazardous Waste No.: None

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): None

### Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

### Superfund Amendments and Reauthorization Act (SARA) Title III

SARA Section 311/312 (40 CFR 370) Hazard Categories: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): 1,2,4-Trimethylbenzene 95-63-6 <1.5%

Section 112 Hazardous Air Pollutants (HAPs): None

### State Regulations

**California:** This product does not contain chemical(s) known to the State of California to cause cancer, birth defects or reproductive harm.

**California and OTC States:** Not for Sale in California. In other jurisdictions, this product is not regulated by consumer regulations.

### New Jersey Right to Know:

Aerosol: Not Applicable

**Bulk:** Solvent Naphtha 64742-94-5 • Naphtha (Petroleum), Hydrotreated Heavy 64742-48-9 • 1, 2, 4-Trimethylbenzene 95-63-6

### International Regulations

**Canadian Environmental Protection Act:** All of the components of this product are included on the Canadian Domestic Substances list (DSL).

### Canadian Workplace Hazardous Materials Information System (WHMIS):

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**WHMIS Classification:** Bulk  
Class B3, Class D2B



### Other Regulations

Montreal Protocol listed ingredients:	None
Stockholm Convention listed ingredients:	None
Rotterdam Convention listed ingredients:	None
RoHS Compliant:	Yes




# MATERIAL SAFETY DATA SHEET

## LPS® PF® HP

Revision Date: February 4, 2011

Supersedes: July 22, 2008

### Section 16 • Other Information

MSDS# 162001 MSDS Preparation Responsible Name: Clea George Regulatory Affairs Coordinator Telephone: +1 770 243-8800	HMIS 1996	HMIS III	<b>NFPA</b>  Flammability  Health      Reactivity
	Health: 1	Health: [1]	
	Flammability: 2	Flammability: aerosol NA Flammability: bulk 2	
	Reactivity 0	Physical Hazard: aerosol NA Physical Hazard: bulk 0	

**Notice to Reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea L. George, Regulatory Affairs Coordinator  
LPS Laboratories, A division of Illinois Tool Works