



LPS 2[®]

HEAVY-DUTY LUBRICANT



FEATURES

- Nondrying, oily film for long lasting lubrication
- Loosens rusted and frozen parts
- Protects against corrosion on steel parts indoors for up to one year
- Displaces moisture
- Excellent protection for hand/machine tools
- Does not contain chlorinated solvents or silicones
- Nonconductive
- Safe on most surfaces
- Acceptable for use in Canadian Food Processing Establishments.
- Inverta Spray Valve

Qualified to: Airbus: TNA 007.10138
Section 10.3.1 • Lockheed G39.04

Conforms to: Pratt & Whitney Canada
CPMC79256 rev. C • Mil-C-16173D
Grade 3 • Mil-C-81309D Type III



Nonfood Compounds Program Listed
Category Code: H2 Registration
#129026 Aerosol, #059848 Bulk

PACKAGES

Net Fill

- 11 oz. (312 grams) aerosol
- 1 gal. (3.78 liters)
- 5 gal. (18.93 liters)
- 55 gal. (208 liters)
- 20 fl.oz (591 ml) trigger spray

Part No.

- 00216
- 02128
- 00205
- 00255
- 00222

APPLICATIONS

- Bearings & Valves
- Cables & Linkages
- Dies, Bits & Fasteners
- Engines & Electric Motors
- Metal Parts
- Parts in Storage
- Production Equipment
- Pulleys & Rollers
- Slides & Tracks



PROPERTIES

Appearance/Physical State:

Clear brown liquid

Dielectric Strength (ASTM D-877):

33 kv

Flash Point (TCC):

175°F (79°C)

HMIS:

1, 2, 0

Pour Point:

- 35°F (- 37°C)

Propellant:

Carbon Dioxide

Specific Gravity (water=1):

0.82 – 0.86

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2014 • Rev. 10/2010