

# LPS® PRESOLVE®

## ORANGE DEGREASER



### FEATURES

- Removes adhesives, grease, wax, tar and dirt
- High performance industrial cleaner which cleans on contact
- Fast acting, deep penetration
- Natural based
- Does not contain chlorinated solvents
- Flash point above 100°F (38°C)
- Non-conductive
- Low residue
- Safe on all metals and most plastics
- Meets or exceeds these specifications: McDonnell Douglas CSD#I, AMS 1525B
- Inverta Spray Valve lets you spray in an upright or inverted position

### PACKAGES

Net Fill	Part No.
15 oz. (425 grams) aerosol	01420
20 fl.oz (591 ml) trigger spray	01422
1 gal. (3.78 liters)	01428
5 gal. (18.93 liters)	01405
55 gal. (208 liters)	01455

### APPLICATIONS

- Air Compressors
- Alternators
- Bearings
- Chains & Cable Connections
- Cranes
- Diesel Engines
- Electric Motors
- Fork Lifts
- Gasoline Engines
- Gears
- Generators
- High Voltage Cables
- Power and Air Tools
- Printing Presses
- Pulleys
- Terminals/Switches



Nonfood Compounds Program Listed  
Category Code: C1 Registration # 129025  
(Aerosol); # 059830 (Bulk)

### PROPERTIES

Flash Point:  
104°F (40°C)

Specific Gravity:  
.803 @ 77°F (25°C)

KB Value:  
53

Ozone Depletion Potential:  
None

Dielectric Strength and  
Breakdown Voltage  
(ASTM D-877):  
>30,000 volts

Propellant:  
Carbon Dioxide



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : [WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)

©2009 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2064 • Rev. 5/2009