



THERMAPLEX® FOODLUBE

BEARING GREASE



FEATURES

- Excellent for use in food processing plants
- NSF® Registered #117848 Category H1
- Uses only FDA listed ingredients
- Acceptable for use in Canadian Food Processing Establishments.
- Extends relubrication intervals
- Resists water washout
- Excellent corrosion protection
- Does not contain solvents or silicone
- Nontoxic, nonstaining, & nonemulsifying
- “Product of the Year” winner for Lubricants World Magazine



Nonfood Compounds Program Listed
Category Code: H1 Registration #117848

PACKAGES

Net Fill	Part No.
14.1 oz. (400 grams) cartridge	70114
35 lbs. (5 gallons) pail	70106
120 lbs. (16 gallons) keg	70135
400 lbs. (55 gallons) drum	70155

APPLICATIONS

- Blending Machines
- Carton Erectors
- Feed Belts
- Filling Equipment
- Frequent Wash Down Area
- Labeling Stations
- Wrapping Equipment

PROPERTIES

4-Ball Weld Load:
>400 kg

Appearance/Physical State:
Creamy Paste

Base Oil Viscosity:
580 SUS @ 100°F
115 cst. @ 40°C
12 cst. @ 100°C

Color:
White

Dropping Point:
500°F (260°C)

Flash Point:
>450°F (232°C) CCC

NLGI Grade:
2

Odor:
Petroleum

Specific Gravity (water=1):
0.96

Temperature Range:
-4°F (-20°C) to 300°F (149°C)

Thickener Type:
Aluminum Complex

Timkin “OK” Load:
40 lbs.

Vapor Density (air=1):
>1

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS® and ThermaPlex® are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2159 • Rev. 10/2010