



WHITE LITHIUM

MULTI-PURPOSE WHITE GREASE



FEATURES

- Contains PTFE additives for superior lubrication
- Rapidly forms into a pure white grease
- Heat and water resistant
- NLGI Grade 2
- Produces a long lasting, protective film against rust and corrosion
- White color allows easy visual inspection
- Does not contain any chlorinated solvents

APPLICATIONS

- Automotive
- Aviation
- Cables
- Cams and Pistons
- Chains
- Guide Rails
- Latches
- Marine
- Open Gears
- Overhead Door Tracks
- Packaging
- Slide Conveyors

PROPERTIES



Boiling/Condensation point:

70.2°C (158°F)

Color:

White

Coefficient of Oil/

Water Distribution:

<1

Dropping Point:

360°F (182°C)

Evaporation rate:

<1 (ethyl ether=1)

Four Ball EP Weld Point (ASTM D-2266):

200 kgf

Four Ball Wear (ASTM D-226):

0.82 mm

NLGI Grade:

No. 2

Odor:

Mild, mineral oil

Specific gravity:

0.78-0.80 (Water=1)

Vapor density:

Approx. 3.0

Vapor pressure:

40 – 50 psia

Volatility:

77% (v/v)

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

PACKAGE

Net Fill

10 oz. (284 grams) aerosol

Part No.

03816

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2112 • Rev. 9/2009