



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** LPS® Food Grade Machine Oil

### Other means of identification

**Part Number** 01316, M01316

### Recommended use of the chemical and restrictions on use

**Recommended use** A spray lubricant designed to displace moisture from mechanical and electrical equipment and provide a light-duty lubrication in food processing applications.

**Restrictions on use** Not available.

### Details of manufacturer or importer

#### Manufacturer

**Supplier Name** MRO Chem Pty Ltd.  
**Address** Level 19, 644 Chapel Street  
South Yarra, Victoria 3141, Australia  
Tel: +03 9823 6273

**In Case of Emergency** +04 3448 1129

#### Manufacturer

**Company name** ITW Pro Brands  
**Address** 4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)  
**Website** <http://www.lpslabs.com>  
**E-mail** [lpssds@itwprobrands.com](mailto:lpssds@itwprobrands.com)


## 2. Hazard(s) identification

### Classification of the hazardous chemical

|                              |  |                              |
|------------------------------|--|------------------------------|
| <b>Physical hazards</b>      | Flammable aerosols<br>Gases under pressure | Category 1<br>Compressed gas |
| <b>Health hazards</b>        | Aspiration hazard                          | Category 1                   |
| <b>Environmental hazards</b> | Not classified.                            |                              |

### Label elements, including precautionary statements

#### Hazard symbol(s)



**Signal word** Danger

**Hazard statement(s)** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

#### Precautionary statement(s)

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**Response** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

**Storage** Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards which do not result in classification** None known.

**Supplemental information** 2.55% of the mixture consists of component(s) of unknown acute oral toxicity. 2.55% of the mixture consists of component(s) of unknown acute inhalation toxicity. 2.55% of the mixture consists of component(s) of unknown acute dermal toxicity.

### 3. Composition/information on ingredients

#### Mixture

| Identity of chemical ingredients          | CAS number and other unique identifiers | Concentration of ingredients |
|---|---|------------------------------|
| Distillates Petroleum, Hydrotreated Light | 64742-47-8                              | 50 - 60                      |
| White Mineral Oil                         | 8042-47-5                               | 30 - 40                      |
| Carbon Dioxide                            | 124-38-9                                | 1 - 3                        |

### 4. First-aid measures

#### Description of necessary first aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** No specific first aid measures noted.

**Ingestion** Not likely, due to the form of the product.

**Personal protection for first-aid responders** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

**Symptoms caused by exposure** Aspiration may cause pulmonary edema and pneumonitis.

**Medical attention and special treatment** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media** Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for fire fighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire fighting equipment/instructions** In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Hazchem code** 2Y E

**General fire hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**For emergency responders** Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

**7. Handling and storage****Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls and personal protection****Control parameters**

Follow standard monitoring procedures.

**Occupational exposure limits****Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)**

| Components                    | Type | Value                   |
|-------------------------------|------|-------------------------|
| Carbon Dioxide (CAS 124-38-9) | STEL | 54000 mg/m <sup>3</sup> |
|                               | TWA  | 30000 ppm               |
|                               |      | 22500 mg/m <sup>3</sup> |
|                               |      | 12500 ppm               |

**Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)**

| Components                    | Type | Value                   |
|-------------------------------|------|-------------------------|
| Carbon Dioxide (CAS 124-38-9) | STEL | 54000 mg/m <sup>3</sup> |
|                               | TWA  | 30000 ppm               |
|                               |      | 22500 mg/m <sup>3</sup> |
|                               |      | 12500 ppm               |

**ACGIH**

| Components   | Type | Value               | Form     |
|--|------|---------------------|----------|
| Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8) | TWA  | 5 mg/m <sup>3</sup> | Oil mist |

**US. ACGIH Threshold Limit Values**

| Components                    | Type | Value     |
|-------------------------------|------|-----------|
| Carbon Dioxide (CAS 124-38-9) | STEL | 30000 ppm |
|                               | TWA  | 5000 ppm  |

**UK. EH40 Workplace Exposure Limits (WELs)**

| Components                    | Type | Value                   |
|-------------------------------|------|-------------------------|
| Carbon Dioxide (CAS 124-38-9) | STEL | 27400 mg/m <sup>3</sup> |
|                               | TWA  | 15000 ppm               |
|                               |      | 9150 mg/m <sup>3</sup>  |
|                               |      | 5000 ppm                |

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

| <b>Components</b>  | <b>Type</b> | <b>Value</b>           | <b>Form</b>                 |
|--|-------------|------------------------|-----------------------------|
| Carbon Dioxide (CAS 124-38-9)                              | TWA         | 9100 mg/m <sup>3</sup> |                             |
| Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8) | TWA         | 5000 ppm               | Respirable aerosol fraction |
|  |             | 5 mg/m <sup>3</sup>    |                             |
| White Mineral Oil (CAS 8042-47-5)                          | TWA         | 350 mg/m <sup>3</sup>  | Vapor.                      |
|  |             | 50 ppm                 | Vapor.                      |
|  |             | 5 mg/m <sup>3</sup>    | Respirable fraction.        |

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, for example personal protective equipment (PPE)**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Wear appropriate chemical resistant gloves.

**Other**

Wear suitable protective clothing.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

**Appearance**

**Physical state**

Gas.

**Form**

Aerosol.

**Color**

Clear. Colorless.

**Odor**

Slight petroleum odor.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

> 435.2 °F (> 224 °C)

**Flash point**

> 158.0 °F (> 70.0 °C) Tag Closed Cup

**Evaporation rate**

< 0.1 BuAc

**Flammability (solid, gas)**

Flammable gas.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)**

0.6 %

**Flammability limit - upper (%)**

7 %

**Explosive limit - lower (%)**

Not available.

**Explosive limit - upper (%)**

Not available.

**Vapor pressure**

< 0.05 mm Hg @ 20°C

**Vapor density**

4.7

**Relative density**

Not available.

|   |   |
|---|---|
| <b>Solubility(ies)</b>                        |   |
| Solubility (water)                            | Not soluble in water  |
| Partition coefficient (n-octanol/water)       | < 1   |
| Auto-ignition temperature                     | > 442.4 °F (> 228 °C)                                       |
| Decomposition temperature                     | Not available.  |
| Viscosity                                     | 130 - 160 cP  |
| Viscosity temperature                         | 77 °F (25 °C)   |
| <b>Other physical and chemical parameters</b> |   |
| Explosive properties                          | Not explosive.  |
| Heat of combustion                            | > 30 kJ/g   |
| Oxidizing properties                          | Not oxidizing.  |
| Percent volatile                              | 60 %  |
| Specific gravity                              | 0.81 - 0.83 @ 20°C  |
| VOC   | 0 % per U.S. State and Federal Consumer Product Regulations |

## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.                                   |
| <b>Conditions to avoid</b>                | Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.      |
| <b>Incompatible materials</b>             | Strong oxidizing agents.  |
| <b>Hazardous decomposition products</b>   | Carbon oxides.  |

## 11. Toxicological information

### Information on possible routes of exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.   |
| <b>Skin contact</b> | No adverse effects due to skin contact are expected.   |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation.   |
| <b>Ingestion</b>    | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

**Symptoms related to exposure** Aspiration may cause pulmonary edema and pneumonitis.

**Acute toxicity** May be fatal if swallowed and enters airways.

| Components   | Species | Test Results           |
|--|---------|------------------------|
| Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8) |         |                        |
| <b>Acute</b>   |         |                        |
| <b>Dermal</b>  |         |                        |
| LD50   | Rabbit  | > 2000 mg/kg           |
| <b>Inhalation</b>  |         |                        |
| <i>Vapor</i>   |         |                        |
| LC50   | Rat     | > 4.5 mg/l, 4 Hours    |
| <b>Oral</b>  |         |                        |
| LD50   | Rat     | > 5000 mg/kg           |
| White Mineral Oil (CAS 8042-47-5)                          |         |                        |
| <b>Acute</b>   |         |                        |
| <b>Dermal</b>  |         |                        |
| LD50   | Rabbit  | > 2000 mg/kg, 24 Hours |
| <b>Inhalation</b>  |         |                        |
| LC50   | Rat     | 2.18 mg/l, 4 Hours     |

| Components  | Species  | Test Results |
|---|--|--------------|
| <b>Oral</b><br>LD50                                       | Rat  | > 5000 mg/kg |
| <b>Skin corrosion/irritation</b>                          | Prolonged skin contact may cause temporary irritation.   |              |
| <b>Serious eye damage/irritation</b>                      | Direct contact with eyes may cause temporary irritation.   |              |
| <b>Respiratory or skin sensitization</b>                  |  |              |
| <b>Respiratory sensitization</b>                          | Not a respiratory sensitizer.  |              |
| <b>Skin sensitization</b>                                 | This product is not expected to cause skin sensitization.  |              |
| <b>Germ cell mutagenicity</b>                             | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |              |
| <b>Carcinogenicity</b>                                    | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.                                  |              |
| <b>Reproductive toxicity</b>                              | This product is not expected to cause reproductive or developmental effects.                                     |              |
| <b>Specific target organ toxicity - single exposure</b>   | Not classified.  |              |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.  |              |
| <b>Aspiration hazard</b>                                  | May be fatal if swallowed and enters airways.  |              |
| <b>Chronic effects</b>                                    | Prolonged inhalation may be harmful.   |              |
| <b>Other information</b>                                  | None known.  |              |

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components   | Species  | Test Results  |
|--|--|---|
| Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8) |  |   |
| <b>Aquatic</b>   |  |   |
| Fish   | LC50   | Rainbow trout,donaldson trout (Oncorhynchus mykiss)<br>2.9 mg/l, 96 hours |
| <b>Persistence and degradability</b>                       | No data is available on the degradability of this product. |   |
| <b>Bioaccumulative potential</b>                           |  |   |
| <b>Partition coefficient n-octanol / water (log Kow)</b>   |  |   |
| LPS® Food Grade Machine Oil                                | < 1  |   |
| <b>Mobility in soil</b>                                    | No data available for this product.                        |   |
| <b>Other adverse effects</b>                               | None known.  |   |

## 13. Disposal considerations

**Disposal methods** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transport information

|                                   |                     |
|-----------------------------------|---------------------|
| <b>ADG</b>                        |                     |
| <b>UN number</b>                  | 1950                |
| <b>UN proper shipping name</b>    | Aerosols, flammable |
| <b>Transport hazard class(es)</b> |                     |
| <b>Class</b>                      | 2.1                 |
| <b>Subsidiary risk</b>            | -                   |
| <b>Packing group</b>              | Not applicable.     |
| <b>Environmental hazards</b>      | Not available.      |

**Hazchem code** 2YE  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**RID**

**UN number** 1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Environmental hazards** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

**UN number** 1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Environmental hazards** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**UN number** 1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** Not available.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**ADG**



IATA; IMDG; RID



**General information** Ensure compliance with applicable regulations.

## 15. Regulatory information

### Safety, health and environmental regulations

**National regulations** This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

#### High Volume Industrial Chemicals (HVIC)

|  |   |
|--|---|
| Carbon Dioxide (CAS 124-38-9)                              | 100000 - 999999 TONNES See the regulation for additional information. |
| Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8) | 1000 - 9999 TONNES See the regulation for additional information.     |
| White Mineral Oil (CAS 8042-47-5)                          | 1000 - 9999 TONNES See the regulation for additional information.     |

#### Importation of Ozone Deleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10)

Not listed.

#### National Pollutant Inventory (NPI) substance reporting list

Not listed.

#### Prohibited Carcinogenic Substances

Not regulated.

#### Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

Not listed.

#### Restricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed.

#### Restricted Carcinogenic Substances

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

Carbon Dioxide (CAS 124-38-9) Listed.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Not applicable.

### International Inventories

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada               | Domestic Substances List (DSL)   | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |



| Country(s) or region        | Inventory name  | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Korea                       | Existing Chemicals List (ECL)                                     | Yes                    |
| New Zealand                 | New Zealand Inventory   | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                     | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

**Issue date** 09-03-2015

**Revision date** 12-28-2016

**Disclaimer** ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.