



SAFETY DATA SHEET

1. Identification

Product identifier LPS® Food Grade Electronic Cleaner

Other means of identification

Part Number 58116, M58116

Recommended use of the chemical and restrictions on use

Recommended use A spray cleaner designed to remove dirt, moisture, dust, flux or oxides from the internal components of electronic or precision equipment such as circuit boards.

Restrictions on use Not available.

Details of manufacturer or importer

Manufacturer

Supplier Name

MRO Chem Pty Ltd.

Address

Level 19, 644 Chapel Street
South Yarra, Victoria 3141, Australia
Tel: +03 9823 6273

In Case of Emergency

+04 3448 1129

Manufacturer

Company name

ITW Pro Brands

Address

4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)

Website

<http://www.lpslabs.com>

E-mail

lpssds@itwprobrands.com

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards	Flammable aerosols	Category 2
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure (inhalation)	Category 2 (nervous system)
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 2

Label elements, including precautionary statements

Hazard symbol(s)



Flame

Gas cylinder

Health hazard

Exclamation mark

Environment

Signal word

Warning

Hazard statement(s)

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation. Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. Use personal protective equipment as required.

Response

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None known.

Supplemental information

None known.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Naphtha (petroleum), Hydrotreated Light	64742-49-0	60 - 70
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a)	811-97-2	20 - 30
Isopropanol	67-63-0	1 - 10
N-Hexane	110-54-3	1 - 2
Pentane	109-66-0	1 - 2

4. First-aid measures

Description of necessary first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Personal protection for first-aid responders

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Symptoms caused by exposure

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Medical attention and special treatment

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire fighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Hazchem code	2Y E
General fire hazards	Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

Control parameters Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4240 mg/m3

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1000 ppm 1230 mg/m ³
	TWA	500 ppm 983 mg/m ³
N-Hexane (CAS 110-54-3)	TWA	400 ppm 72 mg/m ³
	TWA	20 ppm
Pentane (CAS 109-66-0)	STEL	2210 mg/m ³
	TWA	750 ppm 1770 mg/m ³ 600 ppm

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4240 mg/m ³
Isopropanol (CAS 67-63-0)	STEL	1000 ppm 1230 mg/m ³
	TWA	500 ppm 983 mg/m ³
N-Hexane (CAS 110-54-3)	TWA	400 ppm 72 mg/m ³
	TWA	20 ppm
Pentane (CAS 109-66-0)	STEL	2210 mg/m ³
	TWA	750 ppm 1770 mg/m ³ 600 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
N-Hexane (CAS 110-54-3)	TWA	50 ppm
Pentane (CAS 109-66-0)	TWA	1000 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4240 mg/m ³
Isopropanol (CAS 67-63-0)	STEL	1000 ppm 1250 mg/m ³
	TWA	500 ppm 999 mg/m ³
N-Hexane (CAS 110-54-3)	TWA	400 ppm 72 mg/m ³
	TWA	20 ppm
Pentane (CAS 109-66-0)	TWA	1800 mg/m ³ 600 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2)	TWA	4200 mg/m ³
	TWA	1000 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Isopropanol (CAS 67-63-0)	TWA	500 mg/m ³ 200 ppm
N-Hexane (CAS 110-54-3)	TWA	180 mg/m ³ 50 ppm
Pentane (CAS 109-66-0)	TWA	3000 mg/m ³ 1000 ppm

Biological limit values

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	25 mg/l	Aceton	Urine	*
	25 mg/l	Aceton	Blood	*
N-Hexane (CAS 110-54-3)	5 mg/l	2,5-Hexandion plus 4,5-Dihydroxy-2-hexanon (nach Hydrolyse)	Urine	*

* - For sampling details, please see the source document.

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
N-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

N-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Gas.

Form

Aerosol.

Color

Clear. Colorless.

Odor

Hydrocarbon-like.

Odor threshold

Not available.

pH

Not applicable.

Melting point/freezing point	Not available.
Initial boiling point and boiling range	136.99 °F (58.33 °C) Dispensed liquid.
Flash point	< 1.4 °F (< -17.0 °C) Tag Closed Cup
Evaporation rate	< 1 BuAc (Ethyl Ether = 1)
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	352.53 mm Hg @ 38°C
Vapor density	> 1 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 10 %
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 3 cSt
Viscosity temperature	77 °F (25 °C)
Other physical and chemical parameters	
Density	5.65
Explosive properties	Not explosive.
Heat of combustion	> 30 kJ/g
Oxidizing properties	Not oxidizing.
Percent volatile	100 %
Specific gravity	0.68
VOC	74 % per US State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on possible routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to exposure	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Skin irritation. May cause redness and pain.

Acute toxicity

Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Oral		
LD50	Rat	4.7 g/kg
Naphtha (petroleum), Hydrotreated Light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
N-Hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 5 ml/kg, 4 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	73860 ppm, 4 Hours
Oral		
LD50	Rat	49 ml/kg
Pentane (CAS 109-66-0)		
Acute		
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 25.3 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens		
Isopropanol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (nervous system) through prolonged or repeated exposure by inhalation.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.	
Other information	Symptoms may be delayed.	

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) > 1400 mg/l, 96 hours
N-Hexane (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
Ethane, 1,1,1,2-tetrafluoro-(hfc-134a)	1.06	
Isopropanol	0.05	
N-Hexane	3.9	
Pentane	3.39	
Mobility in soil	No data available for this product.	
Other adverse effects	None known.	

13. Disposal considerations

Disposal methods	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

ADG

UN number	1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No
Hazchem code	None.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

UN number	1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1

Packing group Not applicable.
Environmental hazards No
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number 1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not applicable.
Environmental hazards
Marine pollutant No
EmS Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

ADG



IATA; IMDG; RID



15. Regulatory information

Safety, health and environmental regulations

National regulations

This Safety Data Sheet was prepared in accordance with Australia Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals (23/12/2011).

Australia Medicines & Poisons Appendix E

HYDROCARBONS, LIQUID (CAS 110-54-3)

Australia Medicines & Poisons Schedule 5

HYDROCARBONS, LIQUID, INCLUDING KEROSENE, DIESEL (DISTILLATE), MINERAL TURPENTINE, WHITE PETROLEUM SPIRIT, TOLUENE, XYLENE AND LIGHT MINERAL AND PARAFFIN OILS (BUT EXCLUDING THEIR DERIVATIVES) (CAS 110-54-3)

Australia National Pollutant Inventory (NPI): Threshold quantity

N-Hexane (CAS 110-54-3) 10 TONNES/YR Threshold Category: 1

High Volume Industrial Chemicals (HVIC)

Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2) 1000 - 9999 TONNES See the regulation for additional information.

Isopropanol (CAS 67-63-0) 1000 - 9999 TONNES See the regulation for additional information.

Naphtha (petroleum), Hydrotreated Light (CAS 64742-49-0) 1000 - 9999 TONNES See the regulation for additional information.

N-Hexane (CAS 110-54-3) 10000 - 99999 TONNES See the regulation for additional information.
 Pentane (CAS 109-66-0) 10000 - 99999 TONNES See the regulation for additional information.

Importation of Ozone Deleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10)

Ethane, 1,1,1,2-tetrafluoro-(hfc-134a) (CAS 811-97-2) 9

National Pollutant Inventory (NPI) substance reporting list

Not listed.

Prohibited Carcinogenic Substances

Not regulated.

Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

Not listed.

Restricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed.

Restricted Carcinogenic Substances

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 11-15-2016

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.