

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	LPS® Magnum
Registration number	-
Synonyms	None.
Part Number	M00605
Issue date	01-February-2016
Version number	02
Revision date	17-July-2017
Supersedes date	01-February-2016

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	A specialized lubricant designed to reduce friction, heat, noise and wear between moving parts and to loosen rusted or immovable parts and mechanisms.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier	Alsco Ltd
Company name	Unit 13 Hillmead Industrial Estate
Address	Marshall Road Swindon, Wiltshire United Kingdom SN5 5FZ
Telephone	+44 1793 733 900
In Case of Emergency	+001 703-527-3887
Manufacturer	
Company name	ITW Pro Brands
Address	4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)
Website	http://www.lpslabs.com
e-mail	lpssds@itwprobrands.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification Xn;R65, N;R51/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards			
Aspiration hazard	Category 1		H304 - May be fatal if swallowed and enters airways.
Environmental hazards			
Hazardous to the aquatic environment, long-term aquatic hazard	Category 2		H411 - Toxic to aquatic life with long lasting effects.
Not applicable.			

Hazard summary

Physical hazards	Not classified for physical hazards.
Health hazards	Harmful: may cause lung damage if swallowed. Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Specific hazards	Combustible. Harmful: may cause lung damage if swallowed.
Main symptoms	Aspiration may cause pulmonary oedema and pneumonitis.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Dipropylene glycol monomethyl ether, Distillates Petroleum Hydrotreated Light, Distillates, petroleum, solvent-refined light paraffinic, Petroleum Oil

Hazard pictograms



Signal word Danger

Hazard statements

H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P273 Avoid release to the environment.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P331 Do NOT induce vomiting.
P391 Collect spillage.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None known.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Distillates Petroleum Hydrotreated Light	40 - 50	64742-47-8 265-149-8	-	649-422-00-2	
Classification:		DSD: Xn;R65 CLP: Asp. Tox. 1;H304			
Petroleum Oil	30 - 40	64742-52-5 265-155-0	-	649-465-00-7	Note L
Classification:		DSD: Carc. Cat. 2;R45 CLP: Asp. Tox. 1;H304, Carc. 1B;H350			L L
Distillates, petroleum, solvent-refined light paraffinic	1 - 5	64741-89-5 265-091-3	-	649-455-00-2	
Classification:		DSD: Carc. Cat. 2;R45 CLP: Carc. 1B;H350			L L
Dipropylene glycol monomethyl ether	1 - 3	34590-94-8 252-104-2	-	-	#
Classification:		DSD: - CLP: Eye Irrit. 2;H319			
Distillates, petroleum, hydrotreated light paraffinic	< 0,3	64742-55-8 265-158-7	-	649-468-00-3	Note L
Classification:		DSD: Carc. Cat. 2;R45 CLP: Acute Tox. 3;H331, Carc. 1B;H350			L L

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO)

Note N: The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.

Eye contact Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control centre immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness, and discomfort. Aspiration may cause pulmonary oedema and pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Combustible liquid.

5.1. Extinguishing media

Suitable extinguishing media Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Fire may produce irritating, corrosive and/or toxic gases.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire, cool tanks with water spray. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods In the event of fire and/or explosion do not breathe fumes. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protection recommended in Section 8 of the SDS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapours or divert vapour cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from sources of ignition - No smoking. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, on clothing. Avoid prolonged exposure. Do not use in areas without adequate ventilation. Wear personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Do not handle or store near an open flame, heat or other sources of ignition. Keep container tightly closed. Store in a well-ventilated place. Store locked up. Keep out of the reach of children. Use care in handling/storage.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	Ceiling	614 mg/m ³
		100 ppm
	MAK	307 mg/m ³ 50 ppm

Belgium. Exposure Limit Values.

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	MAC	308 mg/m ³
		50 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	Ceiling	550 mg/m ³
	TWA	270 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TLV	309 mg/m3 50 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3 50 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	310 mg/m3 50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	VME	308 mg/m3 50 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	310 mg/m3 50 ppm	Vapor.
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Vapor. Respirable aerosol fraction
		350 mg/m3 50 ppm	Vapor. Vapor.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	AGW	310 mg/m3 50 ppm	Vapor and aerosol. Vapor and aerosol.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	900 mg/m3
	TWA	150 ppm 600 mg/m3 100 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	308 mg/m3
	TWA	308 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	300 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
		50 ppm

Ireland. Occupational Exposure Limits Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Italy. Occupational Exposure Limits Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	450 mg/m3
	TWA	75 ppm 300 mg/m3 50 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Netherlands. OELs (binding) Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	300 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TLV	300 mg/m3
		50 ppm

Poland. MACs. Regulation regarding maximum permissible concentrations and intensities of harmful factors in the work environment, Annex 1 Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	480 mg/m3
	TWA	240 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266) Components

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	150 ppm
	TWA	100 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	450 mg/m3
	TWA	75 ppm
		300 mg/m3 50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	300 mg/m3
	TWA	50 ppm
		300 mg/m3 50 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

EU Exposure Limit Values: Skin designation

Dipropylene glycol monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Dipropylene glycol monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Use personal protective equipment as required.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection For prolonged or repeated skin contact use suitable protective gloves. Chemical resistant gloves are recommended.

- Other Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.

Respiratory protection No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards Not applicable.

Hygiene measures Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Colour Brown.

Odour Mild. Sweet.

Odour threshold Not available.

pH Not applicable

Melting point/freezing point Not established

Initial boiling point and boiling range 195 °C (383 °F)

Flash point 79,0 °C (174,2 °F) Tag closed cup - dispensed liquid

Evaporation rate < 0,1 BuAc

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0,6 %

Flammability limit - upper (%) 7 %

Vapour pressure < 0,05 mm Hg @ 20°C

Vapour density	4,7 (Air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	< 4 %
Partition coefficient (n-octanol/water)	< 1
Auto-ignition temperature	> 228 °C (> 442,4 °F)
Decomposition temperature	Not available.
Viscosity	< 7 cSt @ 25°C
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information	
Heat of combustion	> 30 kJ/g
Specific gravity	0,85 - 0,87 @ 20°C
VOC	3 % per U.S State and Federal Consumer Product Regulations.

SECTION 10: Stability and reactivity

10.1. Reactivity	Strong oxidising agents.
10.2. Chemical stability	Material is stable under normal conditions. Instability caused by elevated temperatures. Risk of ignition.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. This product may react with oxidizing agents.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Harmful if swallowed. May be fatal if swallowed and enters airways.

Symptoms Aspiration may cause pulmonary oedema and pneumonitis. Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness, and discomfort.

11.1. Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test results
Dipropylene glycol monomethyl ether (CAS 34590-94-8)		
Acute		
Dermal		
LD50	Rat	> 20 ml/kg, Hours
Oral		
LD50	Rat	5,4 ml/kg
Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)		
Acute		
Inhalation		
LC50	Rat	> 3,9 mg/l, 4 Hours
Petroleum Oil (CAS 64742-52-5)		
Acute		
Inhalation		
LC50	Rat	> 3,9 mg/l, 4 Hours
Skin corrosion/irritation	Not classified.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	

Respiratory sensitisation	Not a respiratory sensitizer.
Skin sensitisation	This product is not expected to cause skin sensitisation.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

- Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)
- Distillates, petroleum, solvent-dewaxed heavy paraffinic (CAS 64742-65-0)
- Distillates, petroleum, solvent-refined heavy paraffinic (CAS 64741-88-4)
- Distillates, petroleum, solvent-refined light paraffinic (CAS 64741-89-5)
- Petroleum Oil (CAS 64742-52-5)

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
Mixture versus substance information	Not available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test results
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2,9 mg/l, 96 hours

12.2. Persistence and degradability Not inherently biodegradable.

12.3. Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol/water (log Kow)
LPS® Magnum < 1

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

EU waste code Not available.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

SECTION 14: Transport information

ADR	
14.1. UN number	UN3082
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Distillates Petroleum, Hydrotreated Light)
14.3. Transport hazard class(es)	
Class	9

Subsidiary risk	-
Label(s)	9
Hazard No. (ADR)	90
Tunnel restriction code	E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN3082
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Distillates Petroleum, Hydrotreated Light)
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN3082
14.2. UN proper shipping name	Environmentally Hazardous Liquid, N.o.s. (Distillates Petroleum, Hydrotreated Light)
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.


IATA

14.1. UN number	UN3082
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Distillates Petroleum, Hydrotreated Light)
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	No.
ERG Code	9L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.


IMDG

14.1. UN number	UN3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates Petroleum, Hydrotreated Light), MARINE POLLUTANT
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	Not available.

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

This material is not regulated by any mode of transportation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)

Distillates, petroleum, solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Distillates, petroleum, solvent-refined heavy paraffinic (CAS 64741-88-4)

Distillates, petroleum, solvent-refined light paraffinic (CAS 64741-89-5)

Petroleum Oil (CAS 64742-52-5)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Distillates, petroleum, hydrotreated light paraffinic (CAS 64742-55-8)

Distillates, petroleum, solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Distillates, petroleum, solvent-refined heavy paraffinic (CAS 64741-88-4)

Distillates, petroleum, solvent-refined light paraffinic (CAS 64741-89-5)

Petroleum Oil (CAS 64742-52-5)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations	The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.
National regulations	Not available.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations	Not available.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements or R-phrases and H-statements under Sections 2 to 15	<p>R45 May cause cancer.</p> <p>R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H319 Causes serious eye irritation.</p> <p>H331 Toxic if inhaled.</p> <p>H350 May cause cancer.</p>
Revision information	<p>Product and Company Identification: Product and Company Identification</p> <p>SECTION 2: Hazards identification: Response</p> <p>SECTION 2: Hazards identification: Supplemental label information</p> <p>Composition / Information on Ingredients: Ingredients</p> <p>Regulatory Information: Risk Phrases - Labeling</p> <p>HazReg Data: North America</p> <p>GHS: Classification</p>
Training information	Follow training instructions when handling this material.
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.