



Precision Clean

Multi-Purpose Cleaner/Degreaser



FEATURES

- Super industrial strength removes tough stains and soils
- Does not contain butyl, chlorinated or petroleum solvents, bleach, ammonia, or abrasives
- Alkaline formula inhibits flash rusting
- Rinses clean
- Safe on all surfaces except magnesium
- Add Feature Bullet Here
- VOC compliant in all 50 states
- Nonfood Compounds Program Listed Category Code: C1
Registration #059854

IS (IDENTIFICATION SYSTEM)

APPLICATIONS

- Bilges
- Carbon blocks
- Grease traps
- Exhaust hoods
- Compressors
- Concrete
- Engines
- Tanks
- Hoists
- Tools
- Machinery
- Garage floors
- Drill presses
- Sidewalks
- Driveways
- Ovens

SPECIFICATIONS AND APPROVALS

- Tampa Electric Co.
- Halliburton
- Kimberly-Clark
- Inland Steel
- Timken Steel
- Universal-Leaf
- PPG Glass Mfg.
- Kodak
- Hazelton Pump
- Dresser Rand
- Caterpillar
- NSF
- Honda Corp.
- General Motors Co.
- Ford Motor Co.
- McDonnell Douglas CSD #1
- Lockheed Martin DSDN H01.1578
- FLS Aerospace B757, A32
- British Airways LPSPCCD800
- Boeing D6-17487 Rev. H
- ASTM F-519, Type 1C
- ASTM D-2667
- AMS 1526B
- AMS 1526A

AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
02728	C02728	28 fl. oz. (828 mL)	Trigger	12	27 lbs.
02720	C02720	18 wt. oz./510 g/525 mL	Aerosol	12	18 lbs.
02701	C02701	1 gal. (3.78 L)-concentrate	Bottle	4	38 lbs.
02705	C02705	5 gal. (18.93 L)-concentrate	Pail	1	46 lbs.
02755	C02755	55 gal. (208 L)-concentrate	Drum	1	535 lbs.
02765	C02765	55 gal. (208 L)	Drum	1	535 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS02728 • 180605

INDUSTRIAL DEGREASERS



Precision Clean

Multi-Purpose Cleaner/Degreaser

PROPERTIES	AEROSOL	CONCENTRATE	RTU
Appearance/physical state	Gas/Aerosol	Clear/Liquid	Clear/Liquid
Odor	Citrus	Citrus	Mild/Citrus
Melting point/freezing point	Not available	Not available	Not available
Boiling point/range	212°F (100°C)	212°F (100°C)	212°F (100°C)
Vapor pressure	< 17.5 mm Hg @20°C	< 17.5 mm Hg @20°C	< 17.5 mm Hg @20°C
Partition coefficient	Not available	Not available	Not available
Percent volatile	97%	>90%	96%
pH	12.9	13	12.5
Propellant	Petroleum Gases, Liquified	Not applicable	Not applicable
VOC Content	5.8% per U.S. State and Federal Consumer Product Regulations	1.5% per U.S. State and Federal Consumer Product Regulations	0.38% per U.S. State and Federal Consumer Product Regulations
Color	Greenish-blue	Greenish-blue	Green
Flash point	Not established	Not established	Not established
Density	Not available	8.87 lb/gal	8.44 lb/gal
Evaporation rate	1 BuAc	1 BuAc	1 BuAc
Vapor density	>1	>1	>1
Auto-ignition temperature	Not available	Not available	Not available
Viscosity	< 3 cSt	Not available	Low viscosity comparable to water (water = 1 cST. @ 20°C)
Specific Gravity (water=1)	1 - 1.03 @ 20°C	1.06 @ 20°C	1.01 @ 20°C
Temperature Range °F(°C)	Not available	Not available	Not available
4-Ball Weld Load	Not applicable	Not applicable	Not applicable
Soplubility in Water	100%	100%	100%

DIRECTIONS

(Aerosol) Shake well before using. Spray directly on surface to be cleaned. Allow foam to set 10 to 30 seconds. Wipe of rinse clean. Conductive (water-based). Do not use on energized equipment. If equipment is still dirty or greasy, repeat procedure.
 (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.

Dilution Ratio Product:

Water	Equipment	Applications
1: 4	Parts Washers	Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish
1: 5	Dip Tanks	Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools
1: 7	Tumblers	Drill presses, oily parts, pulleys and wires
1: 10	Ultrasonic	Cleaning electrical parts (Deionized water rinse/dry)
1: 4-20	Steam Cleaner	Engines, parts
1: 60	Trigger Sprayer	Floors, leather and fabrics, tile, walls, wood
1: 40-80	Pressure Washer	Cleaning parts, floors, trucks, etc.
1: 100	Trigger Sprayer	Appliances, formica, general cleaning of glass, walls

HANDLING

Avoid prolonged exposure. Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS02720 • 180605